## Push Fit Fittings made of POM



AquaCare GmbH & Co. KG Am Wiesenbusch 11 • D-45966 Gladbeck • Germany © 0 20 43 - 37 57 58-0 • ■ 0 20 43 - 37 57 58-90 www.aquacare.de • info@aquacare.de


for compressed air and aqueous solutions



## Description

- > push fit system with pressure tubes and fittings
- > for aquaria, glass house tubing and air humidifier
- ➤ for air, R.O. water, sea water, tap water, food approved
- easy mounting without glue; without chemicals; connectors for other tubing (e.g. PVC) available
- $\triangleright$  pressure 0 10 bar (at 20 °C)
- ➤ temperature 0 65 °C
- resistant against diluted acids, and alkalines and sea water
- diameters 6, 10, 15, 22 mm
- > easy assembling, easy disassembling, parts are re-usable, easy cleaning

## Assembly / Disassembly



The pressure tube is pushed into the push fit fitting until it cannot be pushed further. The tube should be gently pulled to ensure that the connection is sound. The connection can be released by pushing back the collet and pulling the tube out.

## Product Overview

Straight connector with male thread Series PM01	Straight connector with female thread Series PM45	Bulk connector Series PM12
T connector Series PM02	reduced T connector Series PM30	Y connector Series PM23
Straight connector Series PM04	Reduced straight connector Series PM20	Straight stem connector Series PM05
Elbow connector Series PM03	Reduced elbow connector Series PM21	Stem reducer Series06
Stem elbow connector Series PM22	Hose connector with stem Series PM25	Plug with stem Series PM08
Plug Series PM46	Flow bend clip Series PM26	