

Sediment filter made of stainless steel for cartridges d 2.5"



AquaCare GmbH & Co. KG
 Am Wiesenbusch 11 - D-45966 Gladbeck - Germany
 Tel.: +49 20 43 - 3 75 75 80 Fax: +49 20 43 - 3 75 75 89
 www.aquacare.de e-mail: info@aquacare.de



- High grade stainless steel housing
- Appropriate for standard cartridges with diameter 2.5"
- Length 20", 30" and 40"
- Water flow 8...285 m³/h
- Fast lock with v-band (unit 35 m³/h) or with eye screws
- Applicable for drinking water; for R.O. systems and many others
- All water touched parts comply with the food law (LMBG)

Technical data of the AquaCare stainless steel filters:

Type	320	340	720	730	740	1530	1540	2240	4040	6040
Flow in m ³ /h at 0.15 bar differential pressure	8	15	18	25	35	54	70	105	190	285
Working pressure in bar at 20°C	8									
Connectors	2" BSP		2 1/2" BSP			flange DN100		flange DN150		flange DN200
De-aerating / drain	1/2"									
Length in mm	1150	1600	1200	1600	1600	1640	1640	1680	1680	1720
Diameter in mm	168	168	225	225	225	325	325	410		
Size of filter cartridges	20"	40"	20"	30"	40"	30"	40"	40"	40"	40"
Numbers of filter cartridges	3	3	7	7	7	15	15	22	40	60
Diameter of filter cartridges	2,5"									
Empty weight in kg	18	23	28	32	32	52	52	80		
Material	1.4404 / 316 L or 1.4562 / duplex SS									
Surface	Blast cleaned with glass bead									
Closing system	V-lock					flange with eye screws				

Dimensions of the filters:

Type	height A	height B
320	420	250
340	420	250
720	420	250
730	420	250
740	420	250
1530	340	150
1540	340	150
2240	450	200
4040		
6040		